



A close-up photograph of a thick, blue braided rope. The rope is composed of multiple strands, each with a yellow stripe. The braiding is intricate and creates a textured, three-dimensional appearance. The background is a blurred continuation of the rope.

”

## **THE TRADITION OF ROPE MAKING AT BOLATICE DATES BACK TO 1949.**

The gradual development of braided and twisted ropes and cords being used in marine and fishing industry initially, led to transition from natural materials to progressive synthetic fibres with excellent strength and resistance.

# CONTENT



## BRAIDED ROPES (12 and 8 strand)

HMPE .....	6
TITAN PLUS .....	7
CRUISER PLUS .....	8
TITAN .....	9
CRUISER .....	10
POLYS .....	11
PP MULTITEX .....	12
POLYPROPYLENE .....	13
POLYAMIDE .....	14
POLYESTER .....	15

## MOORING TAILS AND RING TAILS

EYE SPLICING .....	17
COMPOSITE MATERIAL .....	18
POLYAMIDE MATERIAL .....	19

## TWISTED ROPES (4 and 3 strand)

CRUISER .....	21
POLYAMIDE .....	22
POLYS .....	23
PP MULTITEX .....	24
POLYPROPYLENE .....	25
TITAN PLUS .....	26
POLYESTER .....	27
SISAL .....	28

## TECHNICAL PARAMETERS ..... 29

# LANEX PRODUCES ROPES ESPECIALLY FOR:



**SHIP BUILDING  
INDUSTRY**



**TECHNICAL TEXTILE  
INDUSTRY (NETS)**



**BUILDING AND  
CONSTRUCTION  
INDUSTRY**



**SPORT**



**FISHING  
INDUSTRY**



**MECHANICAL  
ENGINEERING**



**AGRICULTURE**



**HOBBY AND  
LEISURE TIME**

## IN-HOUSE EXTRUSION LINES

Because we produce the basic materials in house – polypropylene tapes, high tenacity fibres MULTITEX and POLYS shaped monofilament we can be very flexible in meeting the needs of our customers, and in developing and improving our products, increasing their parameters, and maintaining a high level of quality control.



## CERTIFIED QUALITY

Our production is certified by renowned institutions, including Germanischer Lloyd. Testing takes place in modern, certified in-house testing rooms. LANEX is also certified according to ISO 9001.

MEG-4



LLOYD'S REGISTER



DNV GL



ČSN EN ISO 9001:2016



ČOS 051672 (AQAP 2110)





# **BRAIDED ROPES**

/ HMPE  
TITAN PLUS / CRUISER PLUS  
TITAN / CRUISER / POLYS  
POLYAMIDE / POLYPROPYLENE  
PP MULTITEX / POLYESTER

# HMPE

High Modulus Polyethylene rope is one of the strongest, most durable and innovative ropes on the market. The HMPE ropes are impregnated with durable coating to reduce abrasion and extend the service life. The extraordinary features and extreme strength of HMPE ropes is a reason for using them as frequent substitute to steel wire ropes. The HMPE ropes go through a special heat and UV resistance treatment. They have an extremely low friction coefficient and highly reduce operation costs. They offer much safer handling solution compared to a standard steel wire ropes.

## PARAMETERS



Fiber	HMPE superior
Specific gravity	0.97 km/dm <sup>3</sup> (floating)
UV resistance	excellent
Abrasion resistance	excellent
Acid resistance	excellent
Alkali resistance	excellent
Chemicals resistance	excellent
Cold and frost resistance	excellent
Water resistance	excellent
Heat resistance	low (135 – 145 °C melting)
Elongation	low (< 4% at break)
Creep at 22 °C	low (0.002% per day)
Antistatic coating	on request
Colors	yellow, black, silver

## 8 STRAND

Diameter  
40 - 72 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
40	5	88.10	128.5	1285.0
42	5 1/4	97.20	142.0	1392.5
44	5 1/2	106.20	155.6	1525.0
46	5 3/4	116.00	168.3	1650.0
48	6	125.50	181.1	1775.0
52	6 1/2	146.40	208.6	2045.0
56	7	168.80	237.7	2330.0
60	7 1/2	192.80	268.8	2635.0
64	8	218.30	300.9	2950.0
68	8 1/2	245.30	335.1	3285.0
72	9	273.80	370.8	3635.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 12 STRAND

Diameter  
2 - 48 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
2	1/12	0.25	0.3	3.4
3	1/8	0.49	0.8	8.0
4	1/2	0.90	1.5	15.0
5	5/8	1.43	2.3	22.5
6	3/4	2.30	4.1	40.0
8	1	4.00	7.0	69.0
10	1 1/4	6.10	10.7	105.0
12	1 1/2	8.70	15.3	150.0
14	1 3/4	11.70	20.4	200.0
16	2	15.10	26.5	260.0
18	2 1/4	19.00	32.1	315.0
20	2 1/2	23.30	38.8	380.0
22	2 3/4	28.00	45.9	450.0
24	3	33.10	53.0	520.0
26	3 1/4	38.60	61.2	600.0
28	3 1/2	44.50	69.9	685.0
30	3 3/4	50.80	79.1	775.0
32	4	57.50	88.2	865.0
34	4 1/4	64.60	98.4	965.0
36	4 1/2	72.20	109.1	1070.0
38	4 3/4	80.10	119.9	1175.0
40	5	88.40	131.0	1285.0
42	5 1/4	97.20	142.0	1392.5
44	5 1/2	106.20	155.6	1525.0
46	5 3/4	116.00	168.3	1650.0
48	6	125.50	181.1	1775.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### Antistatic coating

It is possible to get HMPE ropes with advanced antistatic surface coating for HMPE ropes **on request**. This special coating is water resistant and its application significantly reduces static electricity which is generated on the surface of HMPE ropes.

## APPLICATION

**MARINE** / Mooring / Tow / Winch / Tug

**OFFSHORE** / Heavy lifting



# TITAN PLUS

TITAN PLUS – an advanced braided composite rope with one of the highest tensile strengths on the market. The basic material of the rope is a mixture of Polys and high tenacity polyester fibres. High tenacity polyester multifilament fibres on the surface of the rope strands increase abrasion resistance, resistance to warming-up of the rope surface with subsequent melting of surface fibres and resistance to UV degradation in which way the total service life of the rope is prolonged.

## PARAMETERS



Material	PES high tenacity multifilament and POLYS fibres
Specific gravity	1.14 kg/dm <sup>3</sup>
Floating	no
Melting temperature	260/165 °C

UV resistance	outstanding
Abrasion resistance	outstanding
Water absorption	max. 0.5%
Dry and wet conditions	identical wet and dry conditions

## 8 STRAND

Diameter  
32 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
32	4	68.5	27.3	268.0
36	4 1/2	80.0	34.3	336.0
40	5	108.0	42.8	420.0
44	5 1/2	124.0	50.3	493.0
48	6	148.0	59.5	583.0
52	6 1/2	173.0	69.4	680.0
56	7	201.0	80.1	785.0
60	7 1/2	231.0	91.3	895.0
64	8	268.0	102.0	1000.0
68	8 1/2	296.0	116.3	1140.0
72	9	334.0	129.5	1270.0
76	9 1/2	365.0	139.2	1365.0
80	10	411.0	158.1	1550.0
84	10 1/2	454.0	172.4	1690.0
88	11	497.0	190.7	1870.0
92	11 1/2	543.5	208.1	2040.0
96	12	590.0	225.4	2210.0
100	12 1/2	652.0	229.5	2250.0
104	13	714.0	233.6	2290.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 12 STRAND

Diameter  
18 - 44 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
18	2 1/4	21.4	8.6	84.5
20	2 1/2	27.0	10.9	107.0
24	3	38.3	15.3	150.0
28	3 1/2	55.0	21.5	211.2
32	4	68.5	28.2	276.0
36	4 1/2	80.0	35.3	346.0
40	5	108.0	44.1	432.6
44	5 1/2	124.0	51.8	507.8

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Towing lines / Offshore lines / Mooring lines / Mooring tails

# CRUISER PLUS

Cruiser Plus is very high tensile strength rope in comparison with standard ropes which allows to use ropes with smaller diameters which require less storage space. In addition, the rope exhibits better handling properties and non-rotating behavior in both dry and wet conditions.

## PARAMETERS

### Material

PES high tenacity multifilament and POLYS fibres

### Specific gravity

0.99 kg/dm<sup>3</sup>

### Floating

yes

### Melting temperature

260/165 °C

### UV resistance

outstanding



### Abrasion resistance

outstanding

### Durability

outstanding

### Water absorption

max. 0.1%

### Dry and wet conditions

identical wet and dry

conditions

## 8 STRAND

Diameter  
32 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
32	4	68.5	26.3	258.0
36	4 1/2	79.5	35.2	345.0
40	5	96.6	42.5	417.0
44	5 1/2	112.0	49.2	482.0
48	6	128.0	55.7	546.0
52	6 1/2	149.0	62.5	613.0
56	7	169.0	72.7	713.0
60	7 1/2	190.0	81.2	796.0
62	7 3/4	200.5	84.6	830.0
64	8	211.0	90.4	886.0
68	8 1/2	246.0	104.6	1025.0
72	9	267.0	115.8	1135.0
76	9 1/2	315.0	134.1	1315.0
80	10	348.0	147.7	1448.0
84	10 1/2	381.5	157.1	1540.0
88	11	415.0	182.6	1790.0
92	11 1/2	452.0	194.0	1902.0
96	12	489.0	205.4	2014.0
100	12 1/2	526.0	216.6	2124.0
104	13	563.0	228.0	2235.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 12 STRAND

Diameter  
16 - 48 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
16	2 1/4	14.4	7.4	73.0
18	2 1/4	19.8	11.2	110.0
20	2 1/2	20.5	11.7	115.0
24	3	34.5	13.6	133.0
28	3 1/2	45.5	17.9	175.1
32	4	72.5	26.6	261.0
36	4 1/2	79.5	36.0	353.0
40	5	96.6	43.0	422.0
44	5 1/2	112.0	50.6	496.0
48	6	124.5	56.4	553.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Towing lines / Offshore lines / Mooring lines / Mooring tails





## BRAIDED ROPES

# TITAN

TITAN consists of high tenacity polyolefin fibres – POLYS in the cores of the rope strands and high tenacity PES multifilament fibres on the surface of the rope strands and meets the requirements of the standard applicable to composite ropes. Its extreme strength as well as its excellent resistance to abrasion, UV radiation and temperature lend a new use dimension to the rope. The rope is very pleasant to the feel and very good for splicing of eyes.

### PARAMETERS



Material	PES high tenacity multifilament and POLYS fibres
Specific gravity	1.15 kg/dm <sup>3</sup>
Floating	no
Melting temperature	260/165 °C

UV resistance	outstanding
Abrasion resistance	outstanding
Durability	outstanding
Water absorption	max. 0.7%
Dry and wet conditions	identical wet and dry conditions

### 8 STRAND

Diameter  
32 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
32	4	55.2	24.8	242.8
36	4 1/2	71.7	29.1	285.5
40	5	88.5	35.9	351.8
44	5 1/2	107.0	43.0	421.8
48	6	127.0	50.0	490.0
52	6 1/2	150.0	57.8	567.0
56	7	173.0	66.2	649.3
60	7 1/2	199.0	75.7	742.0
64	8	227.0	85.7	840.0
68	8 1/2	256.0	96.0	941.3
72	9	287.0	107.6	1055.3
76	9 1/2	320.0	120.0	1176.0
80	10	354.0	132.3	1296.8
88	11	428.0	158.7	1555.8
96	12	510.0	184.1	1805.0
100	12 1/2	564.0	188.2	1845.0
104	13	617.6	191.6	1878.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### 12 STRAND

Diameter  
18 - 48 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
18	2 1/4	17.9	7.6	74.8
20	2 1/2	22.1	9.3	91.6
24	3	31.9	13.1	128.4
28	3 1/2	48.0	18.8	184.0
32	4	55.2	25.6	250.8
36	4 1/2	71.7	30.1	295.0
40	5	88.5	37.1	363.4
44	5 1/2	107.0	44.4	435.7
48	6	127.0	51.6	506.2

Spliced Termination: -10% / BL is in accordance with ISO 2307

### APPLICATION

/ Towing lines / Offshore lines / Mooring lines / Mooring tails

# CRUISER

CRUISER is high tensile strength rope. Very high strength in comparison with standard polypropylene rope (up to 60% higher). Excellent strength-to-weight ratio of the rope. Economical ratio between BL and weight.

## PARAMETERS

Material	PES high tenacity multifilament and POLYS fibres
Specific gravity	0.99 kg/dm <sup>3</sup>
Floating	yes
Melting temperature	260/165 °C



UV resistance	very good
Abrasion resistance	very good
Durability	very good
Water absorption	max. 0.1%
Dry and wet conditions	identical wet and dry conditions

## 8 STRAND

Diameter  
30 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
30	3 3/4	44.9	18.5	181.7
32	4	51.1	21.0	205.8
36	4 1/2	64.4	26.2	257.3
40	5	79.2	33.5	328.8
44	5 1/2	96.8	40.0	392.4
48	6	114.4	47.1	462.0
50	6 1/4	124.3	51.0	500.0
52	6 1/2	134.2	54.8	537.6
56	7	156.2	62.9	616.8
60	7 1/2	179.3	71.4	699.6
64	8	203.5	80.4	788.4
68	8 1/2	231.0	90.2	884.4
72	9	257.4	100.4	984.0
76	9 1/2	288.2	111.1	1089.6
80	10	319.0	121.8	1194.0
88	11	386.1	145.7	1428.0
90	11 1/4	406.0	151.5	1485.0
92	11 1/2	432.4	161.4	1582.5
96	12	458.7	171.4	1680.0
100	12 1/2	499.2	185.5	1818.5
104	13	539.7	198.8	1949.0

Spliced Termination: -10 % / BL is in accordance with ISO 2307

## 12 STRAND

Diameter  
18 - 48 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
18	2 1/4	16.3	7.1	70.0
20	2 1/2	19.8	8.7	85.0
24	3	28.6	11.8	116.0
28	3 1/2	39.5	16.3	160.0
32	4	51.1	21.4	210.0
36	4 1/2	64.4	27.0	265.0
40	5	79.2	34.6	339.0
44	5 1/2	96.8	40.4	396.0
48	6	112.0	47.7	468.0

Spliced Termination: -10 % / BL is in accordance with ISO 2307

## APPLICATION

/ Towing lines / Offshore lines / Mooring lines / Mooring tails



## BRAIDED ROPES

# POLYS

Modern material rope produced from our own high quality mixed Polyolefin made on our extrusion lines. This rope has very good strength and abrasion resistance, very good resistance to chemicals, easy maintenance, wide range of colors.

### PARAMETERS



**Material**  
**Specific gravity**  
**Floating**  
**Melting temperature**  
**UV resistance**

POLYS fibres (mixture of PP and PE)  
 0.92 kg/dm<sup>3</sup>  
 yes  
 165 °C  
 good

**Abrasion resistance** good  
**Durability** good  
**Water absorption** max. 0.1%  
**Dry and wet conditions** identical wet and dry conditions

### 8 STRAND

Diameter  
30 - 100 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
30	3 3/4	40.8	17.1	168.0
32	4	46.4	19.1	187.0
34	4 1/4	52.6	21.4	210.0
36	4 1/2	58.7	23.7	232.4
38	4 3/4	65.2	26.7	262.0
40	5	72.5	29.3	287.7
44	5 1/2	87.7	35.0	343.4
48	6	104.0	41.1	406.0
52	6 1/2	122.0	47.9	469.8
56	7	142.0	54.9	538.0
60	7 1/2	163.0	62.7	614.8
64	8	186.0	71.0	696.0
68	8 1/2	210.0	79.6	780.0
72	9	235.0	89.2	874.4
76	9 1/2	262.0	99.4	974.4
80	10	290.0	109.6	1074.5
84	10 1/2	320.5	116.0	1137.4
88	11	351.0	122.4	1200.2
92	11 1/2	384.0	133.5	1308.9
96	12	417.0	144.6	1417.5
100	12 1/2	452.0	155.4	1524.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### 12 STRAND

Diameter  
18 - 48 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
18	2 1/4	16.6	6.6	65.0
20	2 1/2	18.1	8.2	80.0
22	2 3/4	21.9	9.9	97.0
24	3	26.8	11.6	114.0
28	3 1/2	35.5	14.8	145.0
32	4	46.4	19.1	187.0
36	4 1/2	58.7	23.6	231.0
40	5	72.5	28.8	282.0
44	5 1/2	87.7	34.4	337.0
48	6	104.0	40.5	397.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### APPLICATION

/ Towing lines / Mooring lines / Fishing lines

# PP MULTITEX

Modern material rope from high tenacity PP fibres made from our raw material produced from our own extrusion line. This type of rope has very good strength and abrasion resistance, very good resistance to chemicals, easy maintenance and handling, wide range of colors.

## PARAMETERS

Material	PP Multitex
Specific gravity	0.91 kg/dm <sup>3</sup>
Floating	yes
Melting temperature	165 °C
UV resistance	average



Abrasion resistance	good
Durability	good
Water absorption	max. 0.1%
Dry and wet conditions	identical wet and dry conditions

## 8 STRAND

Diameter  
30 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
30	3 3/4	40.7	13.4	131.3
32	4	46.3	15.2	149.1
36	4 1/2	58.6	18.4	180.0
40	5	72.3	23.8	233.0
44	5 1/2	87.5	28.4	278.0
48	6	104.0	33.4	327.0
52	6 1/2	122.0	38.7	379.0
56	7	142.0	44.5	436.0
60	7 1/2	163.0	50.5	495.0
64	8	185.0	56.9	558.0
68	8 1/2	210.0	63.8	625.0
72	9	234.0	70.6	692.0
76	9 1/2	261.0	78.5	770.0
80	10	289.0	86.7	850.0
84	10 1/2	320.0	99.1	974.0
88	11	350.0	96.9	950.0
92	11 1/2	393.5	107.5	1054.0
96	12	417.0	114.3	1121.0
100	12 1/2	453.0	125.3	1228.4
104	13	489.0	131.8	1292.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 12 STRAND

Diameter  
14 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
14	1 3/4	9.70	3.5	34.0
16	2	12.40	4.0	39.0
18	2 1/4	16.20	5.8	57.0
20	2 1/2	19.30	6.9	68.0
22	2 3/4	22.00	7.4	73.0
24	3	26.00	9.1	89.0
28	3 1/2	35.40	11.7	115.0
32	4	46.30	17.1	168.0
36	4 1/2	58.60	20.7	203.0
40	5	72.30	23.8	233.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Towing lines / Offshore lines / Mooring lines / Mooring tails



## BRAIDED ROPES

The Polypropylene ropes are the general purpose ropes which have a good strength, are good UV-light and weather resistance, easy to handling and do not absorb water.

# POLY PROPYLENE

### 8 STRAND

Diameter  
30 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
30	3 3/4	40.7	13.5	132.0
32	4	46.3	15.3	150.1
34	4 1/4	52.7	17.1	168.0
36	4 1/2	58.6	19.1	187.0
38	4 3/4	65.5	21.2	208.3
40	5	72.3	23.3	228.5
42	5 1/4	80.0	25.8	253.0
44	5 1/2	87.5	28.5	279.5
46	5 3/4	96.0	31.1	304.8
48	6	104.0	33.5	328.9
50	6 1/4	113.0	35.4	347.3
52	6 1/2	122.0	38.9	381.8
54	6 3/4	132.0	41.9	410.6
56	7	142.0	44.7	438.2
60	7 1/2	163.0	50.8	498.0
62	7 3/4	174.0	54.0	529.0
64	8	185.0	57.2	561.2
66	8 1/4	197.3	60.7	595.0
68	8 1/2	210.0	64.3	630.2
70	8 3/4	222.0	67.7	664.0
72	9	234.0	71.3	699.2
76	9 1/2	262.0	79.1	775.1
78	9 3/4	276.0	83.4	818.0
80	10	289.0	86.7	850.0
84	10 1/2	320.0	93.8	920.0
88	11	350.0	102.0	1000.0
92	11 1/2	393.5	113.2	1110.0
96	12	417.0	120.4	1180.0
100	12 1/2	453.0	131.9	1293.0
104	13	489.0	138.7	1360.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### PARAMETERS

Material	PP split film
Specific gravity	0.91 kg/dm <sup>3</sup>
Floating	yes
Melting temperature	165 °C
UV resistance	average
Abrasion resistance	average
Water absorption	max. 0.1%
Dry and wet conditions	identical wet and dry conditions



### 12 STRAND

Diameter  
16 - 48 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
16	2	11.60	4.8	47.0
20	2 1/2	17.60	7.1	70.0
22	2 3/4	21.90	9.4	92.0
24	3	26.00	10.3	101.0
28	3 1/2	35.40	12.0	118.0
30	3 3/4	40.70	14.1	138.0
32	4	44.20	16.1	158.0
36	4 1/2	58.60	19.4	190.5
40	5	72.30	23.8	233.0
42	5 1/4	79.90	26.0	255.3
44	5 1/2	87.50	29.8	292.0
48	6	104.00	34.1	334.8

Spliced Termination: -10% / BL is in accordance with ISO 2307

### APPLICATION

/ Towing lines / Mooring lines / Fishing lines

# POLYAMIDE

Polyamide ropes, thanks to their properties, are able to absorb shock energy, have excellent strength and very good abrasion resistance. In comparison with polyolefin ropes, PA ropes have different properties, such as higher elongation, higher strength, better resistance to different weather conditions.

## PARAMETERS

Material  
Specific gravity  
Floating  
Melting temperature  
UV resistance  
Abrasion resistance  
Durability  
Water absorption  
Dry and wet conditions



PA multifilament fibres  
1.14 kg/dm<sup>3</sup>  
no  
215 °C  
very good  
very good  
good  
4%  
strength declines 10% when wet

## 8 STRAND - HiTen

Diameter  
40 - 96 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
40	5	100.00	40.0	392.0
44	5 1/2	121.00	48.1	471.5
48	6	144.00	58.0	569.0
52	6 1/2	170.00	67.5	662.0
56	7	201.00	77.2	757.3
60	7 1/2	232.00	88.5	867.7
64	8	253.00	101.5	995.0
68	8 1/2	291.50	115.1	1128.0
72	9	330.00	134.7	1320.5
76	9 1/2	362.50	143.6	1407.5
80	10	395.00	158.5	1554.4
84	10 1/2	428.50	175.1	1716.3
88	11	463.50	192.1	1883.1
92	11 1/2	515.00	196.9	1930.0
96	12	570.00	204.0	2000.0
104	13	678.00	214.2	2100.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 12 STRAND

Diameter  
16 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
16	2	16.00	5.9	58.0
20	2 1/2	25.00	8.7	85.0
24	3	36.00	13.1	128.0
28	3 1/2	49.00	16.5	162.0
30	3 3/4	56.00	18.7	183.0
32	4	64.00	22.4	220.0
36	4 1/2	81.00	27.5	270.0
40	5	100.00	33.2	325.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 8 STRAND

Diameter  
30 - 104 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
30	3 3/4	56.00	17.3	170.0
32	4	64.00	20.4	200.0
36	4 1/2	81.00	25.5	250.0
40	5	100.00	30.6	300.0
44	5 1/2	121.00	36.2	355.0
48	6	144.00	43.4	425.0
52	6 1/2	170.00	51.0	500.0
56	7	197.00	57.1	560.0
60	7 1/2	226.00	64.3	630.0
64	8	257.00	72.4	710.0
68	8 1/2	286.50	81.4	798.0
72	9	325.00	91.8	900.0
76	9 1/2	357.00	100.5	985.0
80	10	401.00	114.2	1120.0
84	10 1/2	443.50	124.4	1220.0
88	11	486.00	134.6	1320.0
92	11 1/2	523.50	147.9	1450.0
96	12	578.00	163.2	1600.0
100	12 1/2	624.50	174.4	1710.0
104	13	677.50	189.7	1860.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Towing lines / Mooring lines / Fishing lines



High tenacity polyester ropes and cords are characterized by their excellent resistance to weather conditions, high strength and excellent abrasion resistance, they remain flexible and soft even when wet.

PARAMETERS



Material  
Specific gravity  
Floating  
Melting temperature  
UV resistance

PES multifilament fibres  
1.38 kg/dm<sup>3</sup>  
no  
260 °C  
outstanding

Abrasion resistance outstanding  
Durability very good  
Manipulation good  
Water absorption max. 0.5%  
Dry and wet conditions identical wet and dry conditions

8 STRAND

Diameter  
30 - 96 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
30	3 3/4	68.3	18.9	185.0
32	4	77.7	21.2	208.0
36	4 1/2	98.4	27.5	270.0
40	5	121.0	36.7	360.0
44	5 1/2	147.0	42.3	415.0
48	6	175.0	47.9	470.0
52	6 1/2	205.0	57.1	560.0
56	7	238.0	64.3	630.0
60	7 1/2	273.0	78.5	770.0
64	8	311.0	87.7	860.0
72	9	393.0	102.5	1005.0
80	10	486.0	120.1	1177.0
88	11	588.0	137.7	1350.0
96	12	699.0	155.3	1523.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

12 STRAND

Diameter  
16 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
16	2	19.40	4.7	46.0
20	2 1/2	30.40	7.9	77.0
24	3	43.70	11.2	110.0
26	3 1/4	51.10	13.0	127.0
28	3 1/2	59.50	14.6	143.0
30	3 3/4	68.30	16.4	161.0
32	4	77.70	18.8	184.0
36	4 1/2	98.40	23.5	230.0
40	5	121.00	29.3	287.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

APPLICATION

/ Towing lines / Offshore lines / Mooring lines / Mooring tails

# MOORING TAILS AND RING TAILS

COMPOSITE MATERIAL  
CRUISER / CRUISER PLUS  
TITAN PLUS

POLYAMIDE MATERIAL  
POLYAMIDE




**Mooring tails provide elasticity and shock/energy absorbing within the mooring arrangement and prevent damages to primary mooring line. Used especially in combination with steel or HMPE ropes in mooring, towing and offshore applications.**

All mooring tails are produced according to latest OCIMF regulations with DNV GL class certificate.

## STANDARD LENGTHS PRODUCED

**For ring tails:** 11 m or 22 m effective working length with rope protection. Ring tail breaking loads are in tables on the pages 19 and 20.



**For mooring tails:** 11 m or 22 m effective working length with 2 protected eyes of 2 m or 1 m for mooring tails.





### EYE SPLICING METHOD 1 WITH POLYESTER ROPE PROTECTION

Recommended for: CRUISER / CRUISER PLUS  
TITAN / TITAN PLUS / POLYS / POLYPROPYLENE

### EYE SPLICING METHOD 1 WITH THIMBLE

Recommended for: CRUISER / CRUISER PLUS / TITAN  
TITAN PLUS / POLYS / POLYPROPYLENE

### EYE SPLICING METHOD 2

Recommended for: POLYAMIDE / POLYESTER  
PP MULTITEX / HMPE

### BRUMMEL SPLICE

Recommended for: HMPE ropes with small diameters

### SINGLE BRAIDED TUCK SPLICE METHOD WITH POLYESTER PROTECTION

Recommended for: HMPE / CRUISER / CRUISER PLUS  
TITAN / TITAN PLUS / POLYS / POLYPROPYLENE

### TANDEM BRAIDED TUCK SPLICE METHOD WITH POLYESTER PROTECTION

Recommended for: POLYAMIDE / POLYESTER  
PP MULTITEX

### SINGLE BRAIDED TUCK SPLICE METHOD WITH POLYESTER PROTECTION

Recommended for: HMPE (larger diameters) / CRUISER / TITAN  
CRUISER PLUS / TITAN PLUS / POLYS / POLYPROPYLENE

### TUCK SPLICE

Recommended for: all twisted ropes from our product range



## EYE SPLICING

The eye splice is used to place a permanent loop in the end of a rope, generally for connection purposes to a fixed point. An eye is also used to form the rope around a thimble, which is used to protect the rope, especially when it is to be attached to a shackle, chain or wire rope. We can make full protected eye with polyester tubular cloth and full protected splice with seizing, which increase service life of ropes.

## POSSIBLE SPLICING ADJUSTMENTS:

- splice with seizing
- splicing with thimble
- polyester rope protection
- polyester rope protection with velcro closure

# COMPOSITE MATERIAL

The basic material of the rope is a mixture of Polys and high tenacity polyester fibres. In general, composite has medium elongation (15 - 17% at break), high energy absorption, the rope remains elastic for a longer time. Breaking load in dry is equal as wet. The strength of composite ropes is higher than that of nylon ropes. Due to this fact smaller diameter of rope can be used, providing better and safer handling. As per OCIMF regulation, the required breaking load must be 25% higher than steel rope.

## CRUISER



- high tensile strength rope
- very high strength in comparison with standard polypropylene rope (up to 60% higher)
- excellent strength-to-weight ratio of the rope
- economical ratio between BL and weight.

### 8 STRAND Mooring tails

Diameter	Weight	Spliced break load	
		t	kN
52	134.2	49.3	483.8
56	156.2	56.6	555.1
60	179.3	64.2	629.6
64	203.5	72.4	709.6
68	231.0	81.2	796.0
72	257.4	90.3	885.6
76	288.2	100.0	980.6
80	319.0	109.6	1074.6
88	386.1	131.1	1285.2
90	406.0	136.3	1336.5
92	432.4	145.2	1423.8
96	458.7	154.2	1512.0
100	499.2	166.9	1636.6
104	539.7	178.9	1754.1

Spliced Termination: -10%  
Spliced break load in accordance with ISO 2307

## CRUISER PLUS



- very high MBL compared to other composite ropes
- low weight compared to other composite ropes, best BL/weight ratio
- increased amount of high tenacity polyester
- multifilament fibres on the surface of the rope
- strands significantly increases the abrasion resistance

### 8 STRAND Mooring tails

Diameter	Weight	Spliced break load	
		t	kN
52	149.0	56.3	551.7
56	169.0	65.5	641.7
60	190.0	73.1	716.4
64	211.0	86.4	797.4
68	246.0	94.1	922.5
72	267.0	104.2	1021.5
76	315.0	120.7	1183.5
80	348.0	132.9	1303.2
84	381.5	141.4	1386.0
88	415.0	164.3	1611.0
92	452.0	174.6	1711.8
96	489.0	184.9	1812.6
100	526.0	195.0	1912.1
104	563.0	205.2	2011.5

Spliced Termination: -10%  
Spliced break load in accordance with ISO 2307

**TITAN PLUS**

- strongest among composite ropes
- increased amount of high tenacity polyester
- multifilament fibres on the surface of the rope
- strands significantly increases the abrasion resistance

**8 STRAND Mooring tails**

Diameter	Weight	Spliced break load	
		t	kN
52	173.0	62.4	612.0
56	201.0	72.1	706.5
60	231.0	82.2	805.5
64	268.0	91.8	900.0
68	296.0	104.7	1026.0
72	334.0	116.6	1143.0
76	365.0	125.3	1228.5
80	411.0	142.3	1395.0
88	454.0	155.1	1521.0
90	497.0	171.7	1683.0
92	543.5	187.3	1836.0
96	590.0	202.9	1989.0
100	652.0	206.6	2025.0
104	714.0	210.2	2061.0

Spliced Termination: -10%  
Spliced break load in accordance with ISO 2307

**POLYAMIDE**

- advantage is extra shock absorption, high elongation (25% at break) and excellent UV protection.
- as per OCIMF regulation, the required breaking load must be 37% higher than steel rope.

**8 STRAND Mooring tails**

Diameter	Weight	Spliced break load	
		t	kN
52	170.00	45.9	450.0
56	197.00	51.4	504.0
60	226.00	57.8	567.0
64	257.00	65.2	639.0
68	286.50	73.3	718.2
72	325.00	82.6	810.0
76	357.00	90.4	886.5
80	401.00	102.8	1008.0
88	443.50	112.0	1098.0
90	486.00	121.2	1188.0
92	523.50	133.1	1305.0
96	578.00	146.9	1440.0
100	624.50	157.0	1539.0
104	677.50	170.8	1674.1

Spliced Termination: -10%  
Spliced break load in accordance with ISO 2307

**POLYAMIDE  
MATERIAL**



# TWISTED ROPES

CRUISER / POLYAMIDE / POLYS  
PP MULTITEX / POLYPROPYLENE  
TITAN PLUS / POLYESTER / SISAL

Modern composite rope with excellent strength and abrasion resistance, floating on water, soft to the touch, very good resistance to chemicals, easy to handle and easy maintenance ropes.

## PARAMETERS



**Material** PES high tenacity multifilament and POLYS fibres  
**Specific gravity** 0.99 kg/dm<sup>3</sup>  
**Floating** yes  
**Melting temperature** 260/165 °C

**UV resistance** very good  
**Abrasion resistance** very good  
**Durability** very good  
**Water absorption** max. 0.1%  
**Dry and wet conditions** identical wet and dry conditions

## 3 STRAND

Diameter  
3 - 36 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
3	3/8	0.60	0.3	3.1
4	1/2	1.10	0.5	5.0
5	5/8	1.40	0.7	6.5
6	3/4	2.00	1.0	10.0
8	1	3.30	1.5	14.6
10	1 1/4	5.00	2.3	22.5
12	1 1/2	7.20	3.2	31.8
14	1 3/4	9.90	4.3	42.5
16	2	12.70	5.5	54.4
18	2 1/4	16.30	6.9	68.1
20	2 1/2	19.80	8.4	82.8
22	2 3/4	24.20	10.1	98.9
24	3	28.60	11.8	116.0
26	3 1/4	33.60	13.6	133.8
28	3 1/2	39.10	15.7	153.8
30	3 3/4	44.60	17.9	175.0
32	4	50.60	20.0	196.3
36	4 1/2	63.80	23.0	225.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 4 STRAND

Diameter  
8 - 36 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
8	1	3.30	1.4	14.6
10	1 1/4	5.00	2.2	22.5
12	1 1/2	7.20	3.1	31.8
14	1 3/4	9.90	4.1	42.5
16	2	12.70	5.3	54.4
18	2 1/4	16.30	6.6	68.1
20	2 1/2	19.80	8.0	82.8
22	2 3/4	24.20	9.6	98.9
24	3	28.60	11.2	116.0
26	3 1/4	33.60	13.0	133.8
28	3 1/2	39.10	14.9	153.8
30	3 3/4	44.60	17.0	175.0
32	4	50.60	19.0	196.3
36	4 1/2	63.80	21.8	225.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes

# POLYAMIDE

Polyamide ropes, thanks to their properties, are able to absorb shock energy, have excellent strength and very good abrasion resistance.

## PARAMETERS



Material	PA multifilament fibres
Specific gravity	1.14 kg/dm <sup>3</sup>
Floating	no
Melting temperature	215 °C
UV resistance	very good

Abrasion resistance	very good
Durability	good
Water absorption	4%
Dry and wet conditions	strength declines 10% when wet

### 3 STRAND

Diameter  
2 - 36 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
2	1/4	0.35	0.1	1.4
3	1/3	0.55	0.3	3.0
4	1/2	0.99	0.4	3.8
5	5/8	1.54	0.6	5.6
6	3/4	2.22	0.8	8.0
7	7/8	3.00	1.0	10.2
8	1	3.95	1.4	14.0
10	1 1/4	6.17	2.2	21.2
12	1 1/2	8.88	3.1	30.1
14	1 3/4	12.10	4.1	40.0
16	2	15.80	5.3	51.9
18	2 1/4	20.00	6.6	64.3
20	2 1/2	24.70	8.2	80.0
22	2 3/4	29.90	9.7	95.0
24	3	35.50	11.4	112.0
26	3 1/4	41.70	13.2	129.0
28	3 1/2	48.40	15.3	150.0
30	3 3/4	55.50	17.3	170.0
32	4	63.20	19.6	192.0
36	4 1/2	80.00	24.5	240.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### 4 STRAND

Diameter  
8 - 36 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
8	1	3.95	1.3	13.0
10	1 1/4	6.17	2.1	20.5
12	1 1/2	8.88	2.9	28.0
14	1 3/4	12.10	3.8	37.0
16	2	15.80	5.0	49.0
18	2 1/4	20.00	6.4	63.0
20	2 1/2	24.70	8.0	78.4
22	2 3/4	29.90	9.5	93.1
24	3	35.50	11.3	111.1
26	3 1/4	41.70	13.0	127.6
30	3 3/4	55.50	17.1	167.2
36	4 1/2	80.00	24.0	235.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes



Modern material rope produced from our own high quality mixed Polyolefin made on our extrusion lines. This rope has very good strength and abrasion resistance, very good resistance to chemicals, easy maintenance, wide range of colors.

**PARAMETERS**



**Material** POLYS fibres (mixture of PP and PE)  
**Specific gravity** 0.92 kg/dm<sup>3</sup>  
**Floating** yes  
**Melting temperature** 165 °C  
**UV resistance** good

**Abrasion resistance** good  
**Durability** good  
**Water absorption** max. 0.1%  
**Dry and wet conditions** identical wet and dry conditions

**3 STRAND**

Diameter  
3 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
3	1/3	0.55	0.3	2.7
4	1/2	0.80	0.4	4.0
5	5/8	1.30	0.6	6.0
6	3/4	1.63	0.8	8.3
7	7/8	2.20	1.1	11.2
8	1	2.90	1.5	14.3
10	1 1/4	4.53	2.2	21.6
12	1 1/2	6.52	3.1	30.4
14	1 3/4	8.88	4.2	41.6
16	2	11.60	5.3	52.2
18	2 1/4	14.70	6.7	66.1
20	2 1/2	18.10	8.1	79.7
22	2 3/4	21.90	9.7	95.5
24	3	26.10	11.4	111.6
26	3 1/4	30.60	13.2	129.1
28	3 1/2	35.50	15.0	147.0
30	3 3/4	40.80	17.1	168.0
32	4	46.40	19.1	187.7
36	4 1/2	58.70	21.7	213.1
38	4 3/4	65.20	23.2	227.3
40	5	72.50	24.4	239.6

Spliced Termination: -10% / BL is in accordance with ISO 2307

**4 STRAND**

Diameter  
14 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
14	1 3/4	8.88	3.6	35.0
16	2	11.60	4.4	43.3
18	2 1/4	14.70	5.4	53.1
20	2 1/2	18.10	7.0	68.5
24	3	26.10	9.1	89.6
30	3 3/4	40.80	13.8	135.0
32	4	46.40	15.2	148.8
36	4 1/2	58.70	19.0	186.3
40	5	72.50	23.1	226.3

Spliced Termination: -10% / BL is in accordance with ISO 2307

**APPLICATION**

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes

# PP MULTITEX

Modern material rope from high tenacity PP fibres made from our raw material produced from our own extrusion line. This type of rope has very good strength and abrasion resistance, very good resistance to chemicals, easy maintenance and handling, wide range of colors.

## PARAMETERS

Material	PP multitex
Specific gravity	0.91 kg/dm <sup>3</sup>
Floating	yes
Melting temperature	165 °C
UV resistance	average



Abrasion resistance	good
Durability	good
Water absorption	max. 0.1%
Dry and wet conditions	identical wet and dry conditions

### 3 STRAND

Diameter  
3 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
3	1/8	0.50	0.2	1.8
4	1/2	0.72	0.3	3.2
5	5/8	1.13	0.5	5.3
6	3/4	1.63	0.7	6.7
7	7/8	2.20	0.9	9.0
8	1	2.89	1.2	11.8
10	1 1/4	4.52	1.7	17.0
12	1 1/2	6.51	2.6	25.0
14	1 3/4	8.86	3.4	33.5
16	2	11.60	4.3	42.5
18	2 1/4	14.60	5.4	53.0
20	2 1/2	18.10	6.4	63.0
22	2 3/4	21.90	7.7	75.0
24	3	26.00	9.2	90.0
26	3 1/4	30.60	10.8	106.0
28	3 1/2	35.40	12.0	118.0
30	3 3/4	40.70	13.5	132.0
32	4	46.30	15.3	150.0
36	4 1/2	58.60	19.4	190.0
40	5	72.30	24.1	236.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

### 4 STRAND

Diameter  
10 - 34 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
10	1 1/4	4.52	1.7	16.5
12	1 1/2	6.51	2.3	22.5
14	1 3/4	8.86	3.1	30.0
16	2	11.60	3.9	38.3
18	2 1/4	14.60	4.8	47.5
20	2 1/2	18.10	6.1	60.0
22	2 3/4	21.90	7.2	71.0
24	3	26.00	8.2	80.0
26	3 1/4	30.60	9.7	95.0
28	3 1/2	35.40	10.8	106.0
30	3 3/4	40.70	12.8	125.0
32	4	46.30	14.3	140.0
34	4 1/2	52.40	15.8	155.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes





# POLYPROPYLENE

The Polypropylene ropes are the general purpose ropes which have a good strength, are good UV-light and weather resistance, easy to handling and do not absorb water.

## 3 STRAND

Diameter  
3 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
3	1/3	0.50	0.2	2.0
4	1/2	0.80	0.4	3.8
6	3/4	1.63	0.7	7.0
7	7/8	2.20	0.9	9.3
8	1	2.89	1.2	11.6
10	1 1/4	4.52	1.8	17.2
11	1 3/8	5.50	2.1	20.5
12	1 1/2	6.51	2.5	24.2
13	1 5/8	7.70	2.9	28.0
14	1 3/4	8.86	3.3	32.4
15	1 7/8	10.30	3.8	37.7
16	2	11.60	4.2	41.4
17	2 1/8	13.10	4.7	46.5
18	2 1/4	14.60	5.3	51.9
19	2 3/8	16.40	5.7	56.1
20	2 1/2	18.10	6.4	62.8
22	2 3/4	21.90	7.7	75.2
24	3	26.00	9.0	88.3
26	3 1/4	30.60	10.5	102.5
28	3 1/2	35.40	12.0	117.6
30	3 3/4	40.70	13.6	133.3
32	4	46.30	15.3	150.1
34	4 1/4	52.00	16.7	163.9
36	4 1/2	58.60	19.1	187.0
38	4 3/4	65.20	20.6	201.9
40	5	72.30	23.3	228.5

Spliced Termination: -10% / BL is in accordance with ISO 2307

## PARAMETERS

Material	PP split film
Specific gravity	0.91 kg/dm <sup>3</sup>
Floating	yes
Melting temperature	165 °C
UV resistance	average
Abrasion resistance	average
Water absorption	max. 0.1%
Dry and wet conditions	identical wet and dry conditions



## 4 STRAND

Diameter  
7 - 40 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
7	3/4	2.20	0.9	8.7
8	1	3.00	1.0	9.7
10	1 1/4	4.52	1.6	15.2
12	1 1/2	6.51	2.2	21.5
14	1 3/4	8.86	3.0	29.6
16	2	11.60	3.7	36.6
18	2 1/4	14.60	5.1	49.6
20	2 1/2	18.10	5.7	56.3
22	2 3/4	21.90	6.9	67.5
24	3	26.00	8.0	78.9
26	3 1/4	30.60	9.3	91.3
28	3 1/2	35.40	10.6	103.8
30	3 3/4	40.70	12.1	118.8
32	4	46.30	13.6	133.1
36	4 1/2	58.60	15.3	150.0
40	5	73.20	19.4	190.0

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes

# TITAN PLUS

TITAN PLUS – an advanced twisted composite rope with one of the highest tensile strengths on the market. The basic material of the rope is a mixture of Polys and high tenacity polyester fibres. High tenacity polyester multifilament fibres on the surface of the rope strands increase abrasion resistance, resistance to warming-up of the rope surface with subsequent melting of surface fibres and resistance to UV degradation in which way the total service life of the rope is prolonged.

## PARAMETERS

**Material** PES high tenacity multifilament and POLYS fibres  
**Specific gravity** 1.14 kg/dm<sup>3</sup>  
**Floating** no  
**Melting temperature** 260/165 °C



**UV resistance** outstanding  
**Abrasion resistance** outstanding  
**Water absorption** max. 0.5%  
**Dry and wet conditions** identical wet and dry conditions



## 3 STRAND

Diameter  
3 · 36 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
3	3/8	0.60	0.3	2.9
4	1/2	0.90	0.5	4.5
5	5/8	1.40	0.6	5.9
6	3/4	1.80	0.8	7.8
7	7/8	2.60	1.1	10.5
8	1	3.60	1.4	14.0
10	1 1/4	5.60	2.1	21.0
12	1 1/2	8.10	3.0	29.7
14	1 3/4	11.00	4.1	40.0
16	2	14.40	5.3	51.8
18	2 1/4	18.20	6.6	64.8
22	2 3/4	27.20	9.7	95.0
24	3	32.40	11.4	111.3
26	3 1/4	38.00	13.3	130.0
28	3 1/2	44.10	15.3	149.8
30	3 3/4	50.50	17.4	170.6
32	4	57.50	19.7	193.4
36	4 1/2	72.80	24.7	242.3

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes



High tenacity polyester ropes and cords are characterized by their excellent resistance to weather conditions, high strength and excellent abrasion resistance, they remain flexible and soft even when wet.

**PARAMETERS**



Material	PES multifilament fibres
Specific gravity	1.38 kg/dm <sup>3</sup>
Floating	no
Melting temperature	260 °C
UV resistance	outstanding
Abrasion resistance	outstanding

Durability	very good
Manipulation	good
Water absorption	max. 0.5%
Dry and wet conditions	identical wet and dry conditions

**3 STRAND**

Diameter  
3 - 36 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
3	1/3	0.50	0.2	2.0
4	1/2	1.21	0.3	2.8
5	5/8	1.90	0.4	4.3
6	3/4	2.73	0.6	6.1
8	1	4.85	1.1	10.6
10	1 1/4	7.58	1.7	16.2
12	1 1/2	10.90	2.3	23.0
14	1 3/4	14.90	3.2	30.9
16	2	19.40	4.1	40.0
18	2 1/4	24.60	5.1	50.0
20	2 1/2	30.30	6.2	61.0
22	2 3/4	36.70	7.5	73.1
24	3	43.70	8.8	86.1
26	3 1/4	51.20	10.3	101.0
28	3 1/2	59.40	12.0	118.0
30	3 3/4	68.20	13.5	132.0
32	4	77.60	15.3	150.0
36	4 1/2	98.20	19.4	190.0

Spliced Termination: -10% / BL is in accordance with ISO 2307



**APPLICATION**

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes

# SISAL

The hard fibre rope is more and more replaced by the man-made fibre rope, in spite of this, these ropes still have their appeal for decorative purposes, and in the engineering industry for their ability to absorb oil (i. e. steel wire rope fillers).

## PARAMETERS

Material  
Specific gravity  
Floating  
Melting temperature  
UV resistance



natural fibres  
1.33 – 1.35 kg/dm<sup>3</sup>  
no  
---  
poor

Abrasion resistance poor  
Durability poor  
Water absorption absorb 10%  
Dry and wet conditions identical wet and dry conditions

## 3 STRAND

Diameter  
6 - 30 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
6	3/4	2.49	0.3	2.6
8	1	4.44	0.5	4.5
9	1 1/8	5.61	0.6	5.7
10	1 1/4	6.93	0.7	6.9
12	1 1/2	9.98	1.0	9.9
14	1 3/4	13.60	1.4	13.3
16	2	17.70	1.8	17.2
18	2 1/4	22.50	2.2	21.6
20	2 1/2	27.70	2.7	26.5
22	2 3/4	33.50	3.3	31.9
24	3	39.90	3.9	37.8
26	3 1/4	46.80	4.5	44.2
28	3 1/2	54.30	5.2	51.0
30	3 3/4	62.40	5.9	58.3

Spliced Termination: -10% / BL is in accordance with ISO 2307

## 4 STRAND

Diameter  
10 - 30 mm



Diameter mm	Circ. inch	Weight kg/100 m	BL t	BL kN
10	1 1/4	6.93	0.6	6.2
12	1 1/2	9.98	0.9	8.9
14	1 3/4	13.60	1.2	12.0
16	2	17.70	1.6	15.5
18	2 1/4	22.50	2.0	19.4
20	2 1/2	27.70	2.4	23.9
22	2 3/4	33.50	2.9	28.7
24	3	39.90	3.5	34.0
26	3 1/4	46.80	4.1	39.8
28	3 1/2	54.30	4.7	45.9
30	3 3/4	62.40	5.4	52.5

Spliced Termination: -10% / BL is in accordance with ISO 2307

## APPLICATION

/ Fishing ropes / Auxiliary ropes / Mooring ropes / Towing ropes





# TECHNICAL PARAMETERS

## RELATIVE STRENGTH

Represents the overall strength (in Newtons, formerly in grams) of a rope under tension based on the material type of rope – split film, fibre, monofilament (measured in dtex, formerly in deniers). This allows for individual materials to be compared with one another.

## MELTING TEMPERATURE

This is one of the basic physical characteristics of synthetic materials. Under the influence of heat, synthetic materials can undergo irreversible changes (surface fabric can start to glaze). It is important to keep in mind that rope should not be stored near sources of heat, because it could lead to changes in the underlying strength of the rope.

## MAXIMUM LONG-TERM-USE TEMPERATURE

Refers to the temperature which, over the long term, doesn't damage the product, but which could lead to changes in key technical parameters.

## WORKING LOAD

It is important to differentiate between the maximum breaking strength of a rope, and its working load. Working load is the absolute maximum strain that can be put on a rope. This is based on a given safety coefficient. When working with a modified rope, to lift a load for example, we have to respect the rope's given safety factor, which will in turn give us the rope's working load.

For example: a load-lifting rope with a minimum strength of 1,000 kg and a safety factor of 7:1, has a working load of 143 kg.

## UV RADIATION RESISTANCE

UV radiation causes textile materials to lose strength. Synthetic and natural materials vary in their resistance to UV radiation, or sunlight. Some materials, especially polyolefins, require UV stabilization. According to applicable standards, PP rope stabilized at 100 kLy should lose no more than 50% of its strength after being exposed for a year to 100 kLy of UV intensity. Stabilization can negatively affect rope strength. Our POLYS SunFix ropes are protected even under very high intensities of sunlight. PP multifilament fibre ropes are very resistant to UV radiation.

## ABRASION RESISTANCE

This is important for the strength of the rope, and for judging the condition of the rope during use. It shows how resistant a given rope is to the abrasion caused by sharp edges.

## PACKAGING OF MARINE ROPES

Ropes are delivered in coils, minicoils, hanks and plastic spools.



## FACTORS INFLUENCING ROPE STRENGTH

- rope construction
- rope abrasion – scratched surface fibres can lead to decreasing strength
- chemicals – the strength of ropes made from materials that are not resistant to certain chemicals can be significantly affected – store your ropes away from all chemicals!
- heat – see the table of characteristics – store ropes away from heat sources!
- sun (UV radiation) – store the ropes away from direct sunlight!
- shock load
- splicing – reduces rope strength by about 10%, splicing must be done very carefully
- knots – reduce rope strength around 50% (up to 90% in steel ropes)



### PURPOSE OF USE

	Rope construction	Marine transport - mooring lines	Marine transport - towing lines	Marine transport - auxiliary lines	Yachts and boats	Fishing and fish farming	Transportation cargo handling
HMPE	braided 12 strand	•••	•••				
	braided 8 strand	•••	•••				
TITAN PLUS	braided 12 strand	•••	•••				
	braided 8 strand	•••	•••				
TITAN	braided 12 strand	•••	•••				
	braided 8 strand	•••	•••				
CRUISER PLUS	braided 12 strand	•••	•••				
	braided 8 strand	•••	•••				
CRUISER	braided 12 strand	•••	•••				
	braided 8 strand	••	••				
POLYAMIDE	twisted 3 and 4 strand	••	••	•••		•••	
	braided 12 strand	•••	•••		•••		
POLYESTER	braided 8 strand	•••	•••	•	•••		
	twisted 3 and 4 strand	••	••	•••	•••	••	•••
POLYS	braided 12 strand	••	••			•••	
	braided 8 strand	••	••	••		•••	
POLYPROPYLENE PPM	twisted 3 and 4 strand	•	•	•••		•••	••
	braided 12 strand	••	•		•••		
POLYPROPYLENE	braided 8 strand	•	•	•	••	•	
	twisted 4 and 3 strand	•	•	•••	••	••	•••

••• most suitable for this application    •• suitable for this application    • useable for this application

### ROPE STRENGTH

Rope strength is an important basic characteristic and is measured in N (Newtons) at the point of rupture. Strength can also be measured in kN and daN (kilo-Newtons and deca-Newton (1 kg = 0.981 daN)).

**Maximum strength is in accordance with accepted European standards:**

- EN ISO 1346 – PP split film and PP Multitex
- EN ISO 10572 – Polysteel
- EN ISO 1140 – Polyamid
- EN ISO 1141 – Polyester
- EN ISO 10556 – Polyester/polyolefin dual fibres
- EN ISO 10325 – HMPE

The maximum strength of non-standard ropes is determined on the basis of our own laboratory measurements, and testing equipment certified and controlled by Germanischer Lloyd.

## CARE OF ROPES AND SAFETY OF USE

The following recommendations will assist you both to extend the service life of the ropes and also to increase the safety of use of the ropes.

- 1 Protect the rope against direct contact with rough surfaces, sharp edges, chemical effects and high temperatures.
- 2 Ropes with spliced eyes or ropes connected with splicing decrease the breaking strength only by 10% whereas knot decrease strength by 25 – 55%.
- 3 If possible, store the ropes in a clean and dry environment, protected from direct sunlight.
- 4 Avoid sharp bends of the rope when under tension, as this stresses only about half of the fibres. The minimum rope bend diameter should be six times the rope diameter.
- 5 The maximum abrasion of the ropes occurs in places that were exposed to friction and abrasion for a long time. Therefore it is suitable to check these places and to change the position of the rope regularly in order to provide for uniform stress. The most exposed places are those being in contact with cleats, hawse holes, pulleys, etc.
- 6 Never stand in the direction of the rope tension. If the rope breaks, the released energy can cause severe injuries.

### MARINE ROPES - TECHNICAL PARAMETERS

PARAMETERS	HMPE	TITAN	TITAN PLUS	CRUISER PLUS	CRUISER	POLYAMIDE	POLYESTER	POLYS	PP MULTITEX	POLYPROPYLENE
Standard	EN ISO 10325	EN ISO 10556	EN ISO 10556	EN ISO 10556	EN ISO 10556	EN ISO 10440	EN ISO 10441	EN ISO 10572	EN ISO 1346	EN ISO 1346
Fiber tenacity	30.0 cN/dtex 33.98 g/den	6.5 cN/dtex 7.40 g/den	6.5 cN/dtex 7.40 g/den	6.5 cN/dtex 7.40 g/den	6.5 cN/dtex 7.40 g/den	7.23 cN/dtex 8.20 g/den	7.23 cN/dtex 8.20 g/den	6.62 cN/dtex 7.50 g/den	6.62 cN/dtex 7.50 g/den	4.25 cN/dtex 4.82 g/den
Linear density	0.97 kg/dm <sup>3</sup>	1.15 kg/dm <sup>3</sup>	1.14 kg/dm <sup>3</sup>	0.99 kg/dm <sup>3</sup>	0.99 kg/dm <sup>3</sup>	1.14 kg/dm <sup>3</sup>	1.38 kg/dm <sup>3</sup>	0.92 kg/dm <sup>3</sup>	0.91 kg/dm <sup>3</sup>	0.91 kg/dm <sup>3</sup>
Floating	yes	no	no	yes	yes	no	no	yes	yes	yes
Melting temperature	145 °C	260/165 °C	260/165 °C	260/165 °C	260/165 °C	215 °C	260 °C	165 °C	165 °C	165 °C
Softening temperature	135 °C	225/140 °C	225/140 °C	225/140 °C	225/140 °C	170 °C	225 °C	140 °C	140 °C	140 °C
Max temperature of use	100 °C	120 °C	120 °C	120 °C	120 °C	130 °C	180 °C	100 °C	100 °C	100 °C
Max working temperature	80 °C	100 °C	100 °C	100 °C	100 °C	100 °C	120 °C	80 °C	80 °C	80 °C
UV resistance	very good	outstanding	outstanding	outstanding	very good	very good	outstanding	good	average	average
Abrasion resistance	very good	outstanding	outstanding	outstanding	very good	very good	outstanding	good	good	average

### RESISTANCE OF ROPES

	HMPE	TITAN / TITAN PLUS CRUISER / CRUISER PLUS	POLYS	PP MULTITEX	POLYPROPYLENE	POLYAMIDE	POLYESTER
Resistance to alkalis	excellent	excellent to most	excellent to most	excellent to most	excellent to most	good at low concentration	average at room temperature
Resistance to acids	excellent	good	excellent	excellent	excellent	low at high concentration	predominantly good
Resistance to petroleum based products	excellent	excellent	excellent	excellent	excellent	good	excellent

***Lanex***

LANEX a. s.  
Hlučínská 96/1, 747 23 Bolatice  
Czech Republic

Phone: +420 553 751 352  
E-mail: [lanex@lanex.cz](mailto:lanex@lanex.cz)

[www.lanexhmpe.com](http://www.lanexhmpe.com)

[www.lanex.cz](http://www.lanex.cz)

